

Model		SC-5516IX	SC-4916IX	SC-4316IX
Panel	Size	55 Inches LED Back light	49 Inches LED Back light	43 Inches LED Back light
	Display Area	1200*680mm	1075*600mm	940*530mm
	Display Resolution	1920*1080		
	Aspect Ratio	16:9		
	Brightness	400 cd/m ²	450 cd/m ²	450 cd/m ²
	Contrast	3000:1	3000:1	3000:1
	Color	8bit, 16.7M	16.7 M	8 bit
	Response Time	4.5ms	6.5ms	6.5ms
	Backlight Life Cycle	≥50,000 hours		
	Viewing Angle	178° / 178° / 178° / 178° (L/R/U/D)		
Power	Consumption	150W	90W	70W
	Input	100-240VAC, 50/60HZ		
Dimensions	Dimension	1870*805*75mm	1800*700.5*75mm	1800*640*75mm
	Net Weight	119Kg	91.8Kg	82.6Kg
Other	Panel Cover	Tempering Glass		
	Speaker	2 * 8Ω / 5W		
	Accessories	Power Cord, Remote, Key		
	Working Temperature	0°C ~ 55°C		
	Working Humidity	20% ~ 80%		
	Storage Temperature	-20°C ~ 65°C		
	Storage Humidity	10% ~ 90%		
X86 Solution	I/O Ports	RJ45 X 1, USB 2.0 X 4, Power X 1, Audio out X 1		
	OS	Android		
	Option A	Intel I3, 4G Memory, 500G Storage		
Touch Panel (Optional)	Touch Panel	IR Touch	IR Touch	IR Touch
	Touch Point	6 Points, Max to 10 Points	6 Points, Max to 10 Points	6 Points, Max to 10 Points
	Active Size	1209*680mm	1073.78*604mm	941*529mm
	Touch Medium	Finger	Finger	Finger
	Luminousness	>95%	>95%	>95%
	Resolution	32767*32767	32767*32767	32767*32767
	Mini touch Area	5mm	5mm	5mm
	Touch Precision	2mm	2mm	2mm
	Touch Response Time	≤20ms	≤20ms	≤20ms
	Touch Life Span	No Limit	No Limit	No Limit